

Monthly Report

2024/04/16

비살

Steel Segmentation

Training of Only E-type images

Dataset Overview:

	6 nos
	10 nos
	8 nos
Total	24 nos

SEM Image: $\mathbb{R}^{1660 \times 1640 \times 1}$

Label : $\mathbb{R}^{1660 \times 1640 \times 3}$

Train		Validation		Test	
	4 nos		1 nos		1 nos
	8 nos		1 nos		1 nos
	5 nos		2 nos		1 nos
Total	17 nos	Total	4 nos	Total	3 nos

Steel Segmentation

Training of Only E-type images

Train		Validation		Test	
	4 nos		1 nos		1 nos
	8 nos		1 nos		1 nos
	5 nos		2 nos		1 nos
Total	17 nos	Total	4 nos	Total	3 nos


Augmentations Performed → Sliding Augmentation, Flipping, Rotation (0, 90), Magnify (0, 2.5), Intensity (0-10), Gamma (0-10), Contrast (HE)
(Same Augmentations as done in previous experiments)

Train	4480 nos	SEM Image: $\mathbb{R}^{800 \times 800 \times 1}$
Validation	1120 nos	Label : $\mathbb{R}^{800 \times 800 \times 3}$
Test	3 nos	

Steel Segmentation

Training of Only E-type images

Experiments		
Models	Pixel Accuracy	Dice Score
Vanilla U-Net3+	77.31	75.58
Enhanced U-Net3+	82.09	79.43
ELU-Net	81.41	79.06
Enhanced ELU-Net	86.3	84.09



Enhancements → 7×7 Kernels, Dilated Convolutions, Blur Pooling
Loss → Focal + Jaccard+ MS-SSIM

Steel Segmentation

Training of Only E-type images

Experiments			
Models	Pixel Accuracy		Dice Score
Vanilla U-Net3+	77.31		75.58
Enhanced U-Net3+	82.09	↑ 3.85%	79.43
Enhanced* U-Net3+	81.34	↓ 0.75%	79.02
ELU-Net	81.41		79.06
Enhanced ELU-Net	86.3	↑ 5.03%	84.09
Enhanced* ELU-Net	84.11	↓ 2.19%	81.86

Why
?
(GLU performed well in nuclei segmentation but why is it struggling here?)

Enhancements* → 7 × 7 Kernels, Dilated Convolutions, Blur Pooling, **GLU Activation**
Loss → Focal + Jaccard+ MS-SSIM

Steel Segmentation


Training of Only E-type images

Why
?

Experiments					
Models	Pixel Accuracy		Dice Score		
Vanilla U-Net3+	77.31		75.58	28GB, 21 Mins per epoch	Batch → 16
Enhanced U-Net3+	82.09	↑ 3.85%	79.43	44GB, 42 Mins per epoch	Batch → 16
Enhanced* U-Net3+	81.34	↓ 0.75%	79.02	47GB, 11 Hour per epoch	Batch → 2
ELU-Net	81.41		79.06		
Enhanced ELU-Net	86.3	↑ 5.03%	84.09		
Enhanced* ELU-Net	84.11	↓ 2.19%	81.86		

Noisy Gradient Estimates & Poor Generalization

Choosing your mini-batch size
 → If mini-batch size = m : Batch gradient descent. $(X^{(1)}, Y^{(1)}) = (X, Y)$
 → If mini-batch size = 1 : Stochastic gradient descent. Each example is its own $(X^{(i)}, Y^{(i)}) = (x^{(i)}, y^{(i)}) \dots (x^{(m)}, y^{(m)})$ mini-batch.
 In practice: Sometimes \downarrow out m




Andrew Ng

Enhancements* → 7 × 7 Kernels, Dilated Convolutions, Blur Pooling, **GLU Activation**
 Loss → Focal + Jaccard+ MS-SSIM


Steel Segmentation – LoRA

Training of Only E-type images






Steel Segmentation – LoRA

Training of Only E-type images



Previous Training




{0, 128, 255}

```
[[1, 1, 0, 0, 0, 0, 0, 0, 0, 0],  
[1, [[0, 0, 0, 0, 0, 0, 0, 0, 0, 0],  
[1, [0 [[0, 0, 1, 1, 1, 1, 1, 1, 1, 1],  
[1, [0 [0, 0, 1, 1, 1, 1, 1, 1, 1, 1],  
[1, [0 [0, 1, 1, 1, 1, 1, 1, 1, 1, 1],  
[1, [0 [0, 1, 1, 1, 1, 1, 1, 1, 1, 1],  
[0, [0 [0, 1, 1, 1, 1, 1, 1, 1, 1, 1],  
[0, [0 [0, 1, 1, 1, 1, 1, 1, 1, 1, 1],  
[0, [0 [0, 1, 1, 1, 1, 1, 1, 1, 1, 1],  
[0, [0 [1, 1, 1, 1, 1, 1, 1, 1, 1, 1],  
[0, [0 [1, 1, 1, 1, 1, 1, 1, 1, 1, 1],  
[0, [0 [1, 1, 1, 1, 1, 1, 1, 1, 1, 1]]
```



One-hot

Steel Segmentation – LoRA

Training of Only E-type images



Current Training






bainite



ferrite





martensite



opency

Steel Segmentation – LoRA

Training of Only E-type images



Current Training


collated




The bounding boxes are all stored in a single list

Steel Segmentation – LoRA

Training of Only E-type images



Current Training



collated




Used as Ground Truth Masks

The bounding boxes are all stored in a single list
Used as input prompt

Steel Segmentation – LoRA

Training of Only E-type images




Used the base pre-trained SAM

- ViT B → 91M parameters (selected)
- ViT L → 308M parameters
- ViT H → 636M parameters

Steel Segmentation – LoRA

Training of Only E-type images




Made using Latex

Algorithm 1 LoRA adaptation for SAM (Segment Anything Model)

```
1: Class SAM_LoRA
2:   Properties:
3:     sam_model                                ▷ SAM model instance
4:     rank                                    ▷ Rank of the LoRA matrix
5:     lora_layer                               ▷ List of layers for LoRA
6:     A_weights, B_weights                    ▷ LoRA weights
7:   procedure INITIALIZE(sam_model, rank, lora_layer = None)
8:     assert rank > 0
9:     if lora_layer = None then
10:       lora_layer ← range(len(sam_model.image_encoder.blocks))
11:     end if
12:     A_weights ← empty list
13:     B_weights ← empty list
14:     Freeze parameters in sam_model.image_encoder
15:     for t_layer_i, blk in enumerate(sam_model.image_encoder.blocks) do
16:       if t_layer_i not in lora_layer then
17:         continue
18:       end if
19:       w_qkv_linear ← blk.attn.qkv
20:       Create LoRA layers: w_a_linear_q, w_b_linear_q, w_a_linear_v,
                           w_b_linear_v
21:       Append to A_weights and B_weights
22:       Replace blk.attn.qkv with a new LoRA_qkv instance
23:     end for
24:     Call reset_parameters
25:     self.sam ← sam_model
26:     self.lora_vit ← sam_model.image_encoder
27:   end procedure
```

Steel Segmentation – LoRA

Training of Only E-type images




Algorithm 1 LoRA adaptation for SAM (Segment Anything Model)

```
1: Class SAM_LoRA
2:   Properties:
3:     sam_model                                ▷ SAM model instance
4:     rank                                     ▷ Rank of the LoRA matrix
5:     lora_layer                               ▷ List of layers for LoRA
6:     A_weights, B_weights                    ▷ LoRA weights
7:   procedure INITIALIZE(sam_model, rank, lora_layer = None)
8:     assert rank > 0
9:     if lora_layer = None then
10:       lora_layer ← range(len(sam_model.image_encoder.blocks))
11:     end if
12:     A_weights ← empty list
13:     B_weights ← empty list
14:     Freeze parameters in sam_model.image_encoder
15:     for t_layer_i, blk in enumerate(sam_model.image_encoder.blocks) do
16:       if t_layer_i not in lora_layer then
17:         continue
18:       end if
19:       w_qkv_linear ← blk.attn.qkv
20:       Create LoRA layers: w_a_linear_q, w_b_linear_q, w_a_linear_v,
                           w_b_linear_v
21:       Append to A_weights and B_weights
22:       Replace blk.attn.qkv with a new LoRA_qkv instance
23:     end for
24:     Call reset_parameters
25:     self.sam ← sam_model
26:     self.lora_vit ← sam_model.image_encoder
27: end procedure
```

Steel Segmentation – LoRA

Training of Only E-type images




Algorithm 1 LoRA adaptation for SAM (Segment Anything Model)

```
1: Class SAM_LoRA
2:   Properties:
3:     sam_model                                ▷ SAM model instance
4:     rank                                     ▷ Rank of the LoRA matrix
5:     lora_layer                               ▷ List of layers for LoRA
6:     A_weights, B_weights                    ▷ LoRA weights
7: procedure INITIALIZE(sam_model, rank, lora_layer = None)
8:   assert rank > 0
9:   if lora_layer = None then
10:     lora_layer ← range(len(sam_model.image_encoder.blocks))
11:   end if
12:   A_weights ← empty list
13:   B_weights ← empty list
14:   Freeze parameters in sam_model.image_encoder
15:   for t_layer_i, blk in enumerate(sam_model.image_encoder.blocks) do
16:     if t_layer_i not in lora_layer then
17:       continue
18:     end if
19:     w_qkv_linear ← blk.attn.qkv
20:     Create LoRA layers: w_a_linear_q, w_b_linear_q, w_a_linear_v,
       w_b_linear_v
21:     Append to A_weights and B_weights
22:     Replace blk.attn.qkv with a new LoRA_qkv instance
23:   end for
24:   Call reset_parameters
25:   self.sam ← sam_model
26:   self.lora_vit ← sam_model.image_encoder
27: end procedure
```

If *rank* = 0, then its finetuning

Steel Segmentation – LoRA

Training of Only E-type images



Algorithm 1 LoRA adaptation for SAM (Segment Anything Model)


```
1: Class SAM_LoRA
2:   Properties:
3:     sam_model                                ▷ SAM model instance
4:     rank                                     ▷ Rank of the LoRA matrix
5:     lora_layer                               ▷ List of layers for LoRA
6:     A_weights, B_weights                    ▷ LoRA weights
7: procedure INITIALIZE(sam_model, rank, lora_layer = None)
8:   assert rank > 0
9:   if lora_layer = None then
10:    lora_layer ← range(len(sam_model.image_encoder.blocks))
11:  end if
12:  A_weights ← empty list
13:  B_weights ← empty list
14:  Freeze parameters in sam_model.image_encoder
15:  for t_layer_i, blk in enumerate(sam_model.image_encoder.blocks) do
16:    if t_layer_i not in lora_layer then
17:      continue
18:    end if
19:    w_qkv_linear ← blk.attn.qkv
20:    Create LoRA layers: w_a_linear_q, w_b_linear_q, w_a_linear_v,
    w_b_linear_v
21:    Append to A_weights and B_weights
22:    Replace blk.attn.qkv with a new LoRA_qkv instance
23:  end for
24:  Call reset_parameters
25:  self.sam ← sam_model
26:  self.lora_vit ← sam_model.image_encoder
27: end procedure
```

Aim is to add LoRA weights to the attention blocks

Each block of SAM has one attention block

Steel Segmentation – LoRA

Training of Only E-type images




Algorithm 1 LoRA adaptation for SAM (Segment Anything Model)

```
1: Class SAM_LoRA
2:   Properties:
3:     sam_model                                ▷ SAM model instance
4:     rank                                     ▷ Rank of the LoRA matrix
5:     lora_layer                               ▷ List of layers for LoRA
6:     A_weights, B_weights                    ▷ LoRA weights
7: procedure INITIALIZE(sam_model, rank, lora_layer = None)
8:   assert rank > 0
9:   if lora_layer = None then
10:    lora_layer ← range(len(sam_model.image_encoder.blocks))
11:  end if
12:  A_weights ← empty list
13:  B_weights ← empty list
14:  Freeze parameters in sam_model.image_encoder
15:  for t_layer_i, blk in enumerate(sam_model.image_encoder.blocks) do
16:    if t_layer_i not in lora_layer then
17:      continue
18:    end if
19:    w_qkv_linear ← blk.attn.qkv
20:    Create LoRA layers: w_a_linear_q, w_b_linear_q, w_a_linear_v,
    w_b_linear_v
21:    Append to A_weights and B_weights
22:    Replace blk.attn.qkv with a new LoRA_qkv instance
23:  end for
24:  Call reset_parameters
25:  self.sam ← sam_model
26:  self.lora_vit ← sam_model.image_encoder
27: end procedure
```

Initialize low rank matrices

Steel Segmentation – LoRA

Training of Only E-type images




Algorithm 1 LoRA adaptation for SAM (Segment Anything Model)

```
1: Class SAM_LoRA
2:   Properties:
3:     sam_model           ▷ SAM model instance
4:     rank                 ▷ Rank of the LoRA matrix
5:     lora_layer           ▷ List of layers for LoRA
6:     A_weights, B_weights ▷ LoRA weights
7: procedure INITIALIZE(sam_model, rank, lora_layer = None)
8:   assert rank > 0
9:   if lora_layer = None then
10:    lora_layer ← range(len(sam_model.image_encoder.blocks))
11:  end if
12:  A_weights ← empty list
13:  B_weights ← empty list
14:  Freeze parameters in sam_model.image_encoder
15:  for t_layer_i, blk in enumerate(sam_model.image_encoder.blocks) do
16:    if t_layer_i not in lora_layer then
17:      continue
18:    end if
19:    w_qkv_linear ← blk.attn.qkv
20:    Create LoRA layers: w_a_linear_q, w_b_linear_q, w_a_linear_v,
    w_b_linear_v
21:    Append to A_weights and B_weights
22:    Replace blk.attn.qkv with a new LoRA_qkv instance
23:  end for
24:  Call reset_parameters
25:  self.sam ← sam_model
26:  self.lora_vit ← sam_model.image_encoder
27: end procedure
```

Steel Segmentation – LoRA

Training of Only E-type images




Algorithm 1 LoRA adaptation for SAM (Segment Anything Model)

```
1: Class SAM_LoRA
2:   Properties:
3:     sam_model                                ▷ SAM model instance
4:     rank                                     ▷ Rank of the LoRA matrix
5:     lora_layer                               ▷ List of layers for LoRA
6:     A_weights, B_weights                    ▷ LoRA weights
7:   procedure INITIALIZE(sam_model, rank, lora_layer = None)
8:     assert rank > 0
9:     if lora_layer = None then
10:       lora_layer ← range(len(sam_model.image_encoder.blocks))
11:     end if
12:     A_weights ← empty list
13:     B_weights ← empty list
14:     Freeze parameters in sam_model.image_encoder
15:     for t_layer_i, blk in enumerate(sam_model.image_encoder.blocks) do
16:       if t_layer_i not in lora_layer then
17:         continue
18:       end if
19:       w_qkv_linear ← blk.attn.qkv
20:       Create LoRA layers: w_a_linear_q, w_b_linear_q, w_a_linear_v,
                           w_b_linear_v
21:       Append to A_weights and B_weights
22:       Replace blk.attn.qkv with a new LoRA_qkv instance
23:     end for
24:     Call reset_parameters
25:     self.sam ← sam_model
26:     self.lora_vit ← sam_model.image_encoder
27:   end procedure
```

t_layer_i is the index of the current block,
blk is the block itself

Steel Segmentation – LoRA

Training of Only E-type images




Algorithm 1 LoRA adaptation for SAM (Segment Anything Model)

```
1: Class SAM_LoRA
2:   Properties:
3:     sam_model                                ▷ SAM model instance
4:     rank                                     ▷ Rank of the LoRA matrix
5:     lora_layer                               ▷ List of layers for LoRA
6:     A_weights, B_weights                    ▷ LoRA weights
7:   procedure INITIALIZE(sam_model, rank, lora_layer = None)
8:     assert rank > 0
9:     if lora_layer = None then
10:       lora_layer ← range(len(sam_model.image_encoder.blocks))
11:     end if
12:     A_weights ← empty list
13:     B_weights ← empty list
14:     Freeze parameters in sam_model.image_encoder
15:     for t_layer_i, blk in enumerate(sam_model.image_encoder.blocks) do
16:       if t_layer_i not in lora_layer then
17:         continue
18:       end if
19:       w_qkv_linear ← blk.attn.qkv
20:       Create LoRA layers: w_a_linear_q, w_b_linear_q, w_a_linear_v,
                           w_b_linear_v
21:       Append to A_weights and B_weights
22:       Replace blk.attn.qkv with a new LoRA_qkv instance
23:     end for
24:     Call reset_parameters
25:     self.sam ← sam_model
26:     self.lora_vit ← sam_model.image_encoder
27:   end procedure
```

Check if current block is in LoRA layer else skip

Steel Segmentation – LoRA

Training of Only E-type images




Algorithm 1 LoRA adaptation for SAM (Segment Anything Model)

```
1: Class SAM_LoRA
2:   Properties:
3:     sam_model                                ▷ SAM model instance
4:     rank                                     ▷ Rank of the LoRA matrix
5:     lora_layer                               ▷ List of layers for LoRA
6:     A_weights, B_weights                    ▷ LoRA weights
7:   procedure INITIALIZE(sam_model, rank, lora_layer = None)
8:     assert rank > 0
9:     if lora_layer = None then
10:       lora_layer ← range(len(sam_model.image_encoder.blocks))
11:     end if
12:     A_weights ← empty list
13:     B_weights ← empty list
14:     Freeze parameters in sam_model.image_encoder
15:     for t_layer_i, blk in enumerate(sam_model.image_encoder.blocks) do
16:       if t_layer_i not in lora_layer then
17:         continue
18:       end if
19:       w_qkv_linear ← blk.attn.qkv           Get the q-k-v values from SAM
20:       Create LoRA layers: w_a_linear_q, w_b_linear_q, w_a_linear_v,
                             w_b_linear_v
21:       Append to A_weights and B_weights
22:       Replace blk.attn.qkv with a new LoRA_qkv instance
23:     end for
24:     Call reset_parameters
25:     self.sam ← sam_model
26:     self.lora_vit ← sam_model.image_encoder
27:   end procedure
```

Steel Segmentation – LoRA

Training of Only E-type images




Algorithm 1 LoRA adaptation for SAM (Segment Anything Model)

```
1: Class SAM_LoRA
2:   Properties:
3:     sam_model                                ▷ SAM model instance
4:     rank                                     ▷ Rank of the LoRA matrix
5:     lora_layer                               ▷ List of layers for LoRA
6:     A_weights, B_weights                    ▷ LoRA weights
7:   procedure INITIALIZE(sam_model, rank, lora_layer = None)
8:     assert rank > 0
9:     if lora_layer = None then
10:      lora_layer ← range(len(sam_model.image_encoder.blocks))
11:    end if
12:    A_weights ← empty list
13:    B_weights ← empty list
14:    Freeze parameters in sam_model.image_encoder
15:    for t_layer_i, blk in enumerate(sam_model.image_encoder.blocks) do
16:      if t_layer_i not in lora_layer then
17:        continue
18:      end if
19:      w_qkv_linear ← blk.attn.qkv
20:      Create LoRA layers: w_a_linear_q, w_b_linear_q, w_a_linear_v,
                           w_b_linear_v
21:      Append to A_weights and B_weights
22:      Replace blk.attn.qkv with a new LoRA_qkv instance
23:    end for
24:    Call reset_parameters
25:    self.sam ← sam_model
26:    self.lora_vit ← sam_model.image_encoder
27:  end procedure
```

Create Linear layers to train

Steel Segmentation – LoRA

Training of Only E-type images




Algorithm 1 LoRA adaptation for SAM (Segment Anything Model)

```
1: Class SAM_LoRA
2:   Properties:
3:     sam_model                                ▷ SAM model instance
4:     rank                                     ▷ Rank of the LoRA matrix
5:     lora_layer                               ▷ List of layers for LoRA
6:     A_weights, B_weights                    ▷ LoRA weights
7:   procedure INITIALIZE(sam_model, rank, lora_layer = None)
8:     assert rank > 0
9:     if lora_layer = None then
10:       lora_layer ← range(len(sam_model.image_encoder.blocks))
11:     end if
12:     A_weights ← empty list
13:     B_weights ← empty list
14:     Freeze parameters in sam_model.image_encoder
15:     for t_layer_i, blk in enumerate(sam_model.image_encoder.blocks) do
16:       if t_layer_i not in lora_layer then
17:         continue
18:       end if
19:       w_qkv_linear ← blk.attn.qkv
20:       Create LoRA layers: w_a_linear_q, w_b_linear_q, w_a_linear_v,
                           w_b_linear_v
21:       Append to A_weights and B_weights
22:       Replace blk.attn.qkv with a new LoRA_qkv instance
23:     end for
24:     Call reset_parameters
25:     self.sam ← sam_model
26:     self.lora_vit ← sam_model.image_encoder
27:   end procedure
```

Steel Segmentation – LoRA

Training of Only E-type images




Algorithm 1 LoRA adaptation for SAM (Segment Anything Model)

```
1: Class SAM_LoRA
2:   Properties:
3:     sam_model                                ▷ SAM model instance
4:     rank                                     ▷ Rank of the LoRA matrix
5:     lora_layer                               ▷ List of layers for LoRA
6:     A_weights, B_weights                    ▷ LoRA weights
7:   procedure INITIALIZE(sam_model, rank, lora_layer = None)
8:     assert rank > 0
9:     if lora_layer = None then
10:       lora_layer ← range(len(sam_model.image_encoder.blocks))
11:     end if
12:     A_weights ← empty list
13:     B_weights ← empty list
14:     Freeze parameters in sam_model.image_encoder
15:     for t_layer_i, blk in enumerate(sam_model.image_encoder.blocks) do
16:       if t_layer_i not in lora_layer then
17:         continue
18:       end if
19:       w_qkv_linear ← blk.attn.qkv
20:       Create LoRA layers: w_a_linear_q, w_b_linear_q, w_a_linear_v,
                           w_b_linear_v
21:       Append to A_weights and B_weights
22:       Replace blk.attn.qkv with a new LoRA_qkv instance
23:     end for
24:     Call reset_parameters
25:     self.sam ← sam_model
26:     self.lora_vit ← sam_model.image_encoder
27:   end procedure
```

Replace updated weights to SAM

Steel Segmentation – LoRA

Training of Only E-type images



- Image is preprocessed based on SAM input requirement
- Bounding Boxes are encoded using SAM's prompt encoder

The inputs into the model – (Image, prompt, target) is processed into tensors

